

**THIS VERSION IS APPLIED FOR SAO VANG IMPORT-EXPORT PRODUCTION
JOINT STOCK COMPANY; VIETNAM ONLY**

WITH SPECIAL DESIGN AND COMPOUND FOR ONLY TRAILER OR SEMI - TRAILER

ALL THESE TYRES IN THESE CATALOGUE CAN NOT BE USED FOR LORRIES TRUCK AND BUSES

GIANR***UI***

JOYALL(WEIHAI) TIRE CO., LTD.



www.joyalltires.com



A608+/A608 **A612/G108+** **UB08+**



Suitable for only trailer or semi-trailer
Designed for long-distance standard transportation on
highway or good paved road



Wear-
Resistant



Uneven
Wear Resistance



Scratch
Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
10.00R20	18	149/146	J	K	1054	272	16.5	3250	930	3000	930	7.5
11.00R20	18	152/149	J	K	1085	284	16.7	3550	930	3250	930	8.0
11R22.5	18	149/146	J	L	1054	270	16.5	3250	930	3000	930	8.25
12R22.5	18	152/149	J	L	1084	292	17.8	3550	930	3250	930	9.00
12R22.5	20	154/151	L	L	1084	292	16.7	3750	970	3450	970	9.00
295/80R22.5	18	152/149	J	L	1045	292	16.8	3550	900	3250	900	9.00
215/75R17.5	16	135/133	H	L	766	212	13.5	2180	850	2060	850	6.00
315/80R22.5	20	157/154	L	K	1076	310	16.5	4125	900	3750	900	9.00



A8/A606 G106



Suitable for only trailer or semi-trailer
Designed for long-distance standard/overload
transportation on good paved road



Wear-
Resistant



Uneven
Wear Resistance



Scratch
Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	16	146/143	H	L	1050	272	16.5	3000	830	2725	830	8.25
12R22.5	18	152/149	J	L	1081	293	16.5	3550	930	3250	930	9.00
295/80R22.5	18	152/149	J	M	1042	295	16.8	3550	900	3250	900	9.00
315/80R22.5	20	157/154	L	L	1076	316	16.5	4125	900	3750	900	9.00
315/70R22.5	18	151/148	J	L	1017	310	16.7	3450	830	3150	830	9.00



A702



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on
highway or good paved road



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
315/70R22.5	18	151/148	J	L	1020	310	23.0	3450	830	3150	830	9.00
315/80R22.5	20	157/154	L	K	1090	316	21.8	4125	900	3750	900	9.00



A703



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on
highway or good paved road



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1085	290	22.0	3550	930	3250	930	9.00



A705/G205 UC05



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation
on highway or good paved road



Wear-
Resistant

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
235/75R17.5	18	143/141	J	L	-	-	15.0	2725	875	2575	875	6.75
295/80R22.5	18	152/149	J	L	1053	290	18.8	3550	900	3250	900	9.00



A706/G206



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on highway or good paved road



Wear-Resistant



Scratch Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1092	290	18.8	3550	930	3250	930	9.00



A709/G209



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation
on highway or good paved road



Wear-
Resistant

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
295/80R22.5	22	160/157	M	L	1072	-	21.8	4500	1000	4125	1000	9.00



A878/G848 **G838/A868**



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on
highway or good paved road



Self-
Cleaning

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
285/75R24.5	16	147/144	H	L	1059	272	21.5	3075	830	2800	830	8.25
295/75R22.5	16	146/143	H	L	1020	288	22.0	3000	830	2725	830	9.00
11R22.5	16	146/143	H	L	1061	272	22.0	3000	830	2725	830	8.25
11R24.5	16	149/146	H	L	1106	268	21.5	3250	830	3000	830	8.25



A888+/A888



Suitable for only trailer or semi-trailer
Designed for mid-long distance standard transportation on paved road at high speed



Wear-Resistant

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
315/80R22.5	20	157/154	L	L	1080	316	22.0	4125	900	3750	900	9.00
315/80R22.5	20	157/154	L	K	1080	316	24.0	4125	900	3750	900	9.00
12R22.5	18	152/149	J	L	1085	293	22.8	3550	930	3250	930	9.00



A88



Suitable for only trailer or semi-trailer
Designed for mid-long distance standard transportation on paved road at high speed



Wear-Resistant

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1089	293	20	3550	930	3250	930	9.00



B878/G201 **G828/A701**



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on
highway or good paved road



Wear-
Resistant



Self-
Cleaning

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	16	146/143	H	L	1061	272	22.0	3000	830	2725	830	8.25
12R22.5	18	152/149	J	L	1086	290	22.0	3550	930	3250	930	9.00
295/80R22.5	18	152/149	J	M	1053	295	22.0	3550	900	3250	900	9.00
315/80R22.5	20	157/154	L	L	1081	312	22.0	4125	900	3750	900	9.00



A605/G105 UB05



Suitable for only trailer or semi-trailer
Designed for long-distance standard transportation
on highway or good paved road



Wear-
Resistant



Uneven
Wear Resistance



Scratch
Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	18	149/146	J	L	1050	260	15.0	3250	930	3000	930	8.25
12R22.5	18	152/149	J	L	1082	290	17.0	3550	930	3250	930	9.00
235/75R17.5	18	143/141	J	J	802	234	13.2	2725	875	2575	875	6.75
235/75R17.5	18	143/141	J	L	802	234	13.2	2725	875	2575	875	6.75
245/70R19.5	18	142/140	J	K	841	246	14.3	2650	900	2500	900	7.50
275/70R22.5	18	152/149	J	J	962	280	15.5	3550	900	3250	900	8.25
275/80R22.5	18	149/146	J	L	1015	280	16.5	3250	900	3000	900	8.25
295/60R22.5	18	150/147	J	L	926	292	17.3	3350	900	3075	900	9.00



A609



Suitable for only trailer or semi-trailer
Designed for long-distance standard transportation on
highway or good paved road



Wear-
Resistant



Uneven
Wear Resistance



Anti-
Skidding

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1080	290	15.3	3550	930	3250	900	9.00



A601



Suitable for only trailer or semi-trailer
Designed for regional mid&short distance overload
transportation on paved road at mid speed



Wear-
Resistant



Self-
Cleaning



Anti-
Skidding

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
385/65R22.5	24	164	N	J	1073.4	386	16.5	5000	900	-	-	11.75



A610/G110



Suitable for only trailer or semi-trailer
Designed for regional mid&short distance overload
transportation on paved road at mid speed



Wear-
Resistant



Self-
Cleaning



Anti-
Skidding

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
385/65R22.5	24	164	N	K	1071.4	386	16.0	5000	900	-	-	11.75
385/65R22.5	24	164	N	J	1071.4	386	16.0	5000	900	-	-	11.75
385/55R22.5	20	160	L	K	996	380	15.0	4500	900	-	-	12.25



A615/G115 UB15



Suitable for only trailer or semi-trailer
Designed for regional mid&short distance overload
transportation on paved road at mid speed



Wear-
Resistant



Self-
Cleaning



Anti-
Skidding



Uneven
Wear Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
385/65R22.5	24	164	N	J	1073	382	15.5	5000	900	-	-	11.75



T810/T800 A875/G845 G835



Suitable for only trailer or semi-trailer
Designed for long-distance standard transportation on
highway or good paved road



Wear-
Resistant



Uneven
Wear Resistance



Anti-
Skidding

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	16	146/143	H	L	1039	272	11.0	3000	830	2725	830	8.25
12R22.5	18	152/149	J	L	1074	290	15.2	3550	930	3250	930	9.00
295/75R22.5	16	146/143	H	L	998	288	11.0	3000	830	2725	830	9.00



A866/ G836 **A602/G846** **A876/G102**



Suitable for only trailer or semi-trailer
Designed for long-distance standard/overload
transportation on good paved road



Wear-
Resistant



Uneven
Wear Resistance



Anti-
Skidding

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	16	146/143	H	L	1047	272	15.0	3000	830	2725	830	8.25
11R24.5	16	149/146	H	L	1093	268	14.8	3250	830	3000	830	8.25
12R22.5	18	152/149	J	L	1074	290	16.2	3550	930	3250	930	9.00
285/75R24.5	16	147/144	H	L	1046	272	14.5	3075	830	2800	830	8.25
295/75R22.5	16	146/143	H	L	1006	288	15.0	3000	830	2725	830	9.00
295/80R22.5	18	152/149	J	M	1039	295	15.0	3550	900	3250	900	9.00
315/80R22.5	20	157/154	L	L	1076	310	15.0	4125	900	3750	900	9.00



A889/E800



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on
highway or good paved road



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1075	290	16.5	3550	930	3250	930	9.00
13R22.5	20	156/153	L	K	1115	308	16.5	4000	930	3650	930	9.75



A507



Suitable for only trailer or semi-trailer
Designed for longdistance overload transportation
on highway or good paved road



Wear-
Resistant



Self-
Cleaning

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1080	290	15.3	3550	930	3250	930	9.00



A506



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on highway or good paved road



Wear-
Resistant

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1082	290	17.5	3550	930	3250	930	9.00



A509/G009



Suitable for only trailer or semi-trailer
Designed for regional medium distance overload
transportation on good paved road



Wear-
Resistant



Self-
Cleaning



Long-
Lasting

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1085	290	18.0	3550	930	3250	930	9.00



UA13 /T801 **B875/T811** **G013**



Suitable for only trailer or semi-trailer
Designed for long-distance overload transportation on highway or good paved road



Low Heat
Buildup



Uneven
Wear Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R24	20	160/157	L	K	1226	304	17.0	4500	900	4125	900	8.5
11R22.5	16	146/143	H	L	1047	272	15.0	3000	830	2725	830	8.25
11R22.5	16	148/145	H	L	1047	272	15.0	3150	850	2900	850	8.25
12R22.5	18	152/149	J	L	1074	290	15.0	3550	930	3250	930	9.00
315/80R22.5	20	157/154	L	L	1076	310	16.0	4125	900	3750	900	9.00



A508



Suitable for only trailer or semi-trailer
Designed for Urban and intercity short distance transport on paved road at mid speed



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	16	148/145	H	J	1060	282	22.0	3150	850	2900	850	8.25



A802



Suitable for only trailer or semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Wear-
Resistant



Long-
Lasting

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
315/80R22.5	20	157/154	L	D	1080	316	22.0	4125	900	3750	900	9.00
315/80R22.5	22	161/157	M	D	1080	316	22.0	4625	900	4125	900	9.00



A803



Suitable for only trailer or semi-trailer
Designed for mid-short distance standard transportation
on mixed road conditions at mid-low speed



Anti-puncture



Self-Cleaning



Uneven
Wear Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	K	1094	293	23.0	3550	930	3250	930	9.00



A805



Suitable for only trailer or semi-trailer
Specially engineered for the toughest road conditions & extra-heavy load



Wear-Resistant



Self-Cleaning

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	16	148/145	H	K	1062	276	23.0	3150	850	2900	850	8.25



A807



Suitable for only trailer or semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Long-
Lasting



Self-
Cleaning

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R24	20	160/157	L	K	1229	308	19.5	4500	900	4125	900	8.5



G315/UD15 A815



Suitable for only trailer or semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



Low Heat
Buildup



Long-
Lasting

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R20	20	156/153	L	J	1125	315	21.3	4000	900	3650	900	8.5
12.00R20	22	158/155	M	G	1125	304	21.3	4250	970	3875	970	8.5
13R22.5	22	158/156	M	G	1125	305	21.3	4250	900	4000	900	9.75
12R22.5	18	152/149	J	G	-	-	20.8	3550	930	3250	930	9.00



G312/UD12 A812 A808 G308



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on mixed road conditions at low speed



Low Heat
Buildup



Long-
Lasting



Grip

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R20	22	158/155	M	G	1125	304	18.8	4250	970	3875	970	8.50
12.00R20	20	156/153	L	J	1125	304	20.3	4000	900	3650	900	8.50
12.00R20	20	156/153	L	K	1125	304	18.8	4000	900	3650	900	8.50
13R22.5	22	158/156	M	G	1125	305	20.3	4250	900	4000	900	9.75
315/80R22.5	20	157/154	L	K	1076	316	23.0	4125	900	3750	900	9.00
315/80R22.5	22	161/157	M	D	1076	316	23.0	4625	900	4125	900	9.00



A958/ A801



Suitable for only trailer or semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
10.00R20	18	149/146	J	K	1058	278	18.0	3250	930	3000	930	7.5
11.00R20	18	152/149	J	K	1085	286	19.0	3550	930	3250	930	8.0
12.00R20	20	156/153	L	K	1124	310	19.0	4000	900	3650	900	8.5
12.00R20	22	158/155	M	G	1124	310	19.0	4250	970	3875	970	8.5
12R22.5	18	152/149	J	K	1085	293	19.0	3550	930	3250	930	9.00
13R22.5	22	158/156	M	G	1124	316	19.0	4250	900	4000	900	9.75



B958/0915



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on mixed road conditions at low speed



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
10.00R20	18	149/146	J	J	1064	278	21.8	3250	930	3000	930	7.5
11.00R20	18	152/149	J	J	1080	286	21.0	3550	930	3250	930	8.0
12.00R20	20	156/153	L	J	1121	310	22.0	4000	900	3650	900	8.5



C958/D901 ***A806***



Suitable for only trailer or semi-trailer
Designed for short distance transportation on mixed road
conditions at mid-low speed

**This product cannot be used for lorries truck and buses.*


Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11.00R20	18	152/149	J	K	1080	284	18.5	3550	930	3250	930	8.00
12.00R20	18	154/151	J	K	1115	308	18.6	3750	830	3450	830	8.50
12.00R20	20	156/153	L	K	1115	308	18.6	4000	900	3650	900	8.50
12R22.5	18	152/149	J	K	1080	290	18.5	3550	930	3250	930	9.00



D909/D900



Suitable for only trailer or semi-trailer
Designed for mid-short distance heavy load transportation
on mixed road conditions at mid-low speed



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11.00R20	18	152/149	J	K	1080	284	18.5	3550	930	3250	930	8.0
12.00R20	20	156/153	L	K	1119	308	20.6	4000	900	3650	900	8.5



A9/E900 **UA10/G010** **A502**



Suitable for only trailer or semi-trailer
 Designed for mid-short distance heavy load transportation
 on paved road at mid-low speed



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
10.00R20	18	149/146	J	K	1054	278	16.0	3250	930	3000	930	7.5
11.00R20	18	152/149	J	K	1080	286	16.5	3550	930	3250	930	8.0
12.00R20	20	156/153	L	K	1120	310	17.0	4000	900	3650	900	8.5
12.00R20	22	158/155	M	G	1120	310	17.0	4250	970	3875	970	8.5
11R22.5	18	149/146	J	L	1054	272	16.0	3250	930	3000	930	8.25
13R22.5	20	156/153	L	K	1120	316	17.0	4000	930	3650	930	9.75
13R22.5	22	158/156	M	G	1120	316	17.0	4250	900	4000	900	9.75



A505



Suitable for only trailer or semi-trailer
Designed for mid&short distance overload transportation
on paved road at mid-low speed



Wear-
Resistant



Self-
Cleaning

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R24	20	160/157	L	K	1226	308	16.0	4500	900	4125	900	8.5



A919



Suitable for only trailer or semi-trailer
Designed for mid-short distance overload transportation
on paved road at mid speed



Anti-
Skidding



Wear-
Resistant

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1081	293	16.5	3550	930	3250	930	9.00
12R22.5	20	154/151	L	L	1081	293	16.5	3750	970	3450	970	9.00



A959



Suitable for only trailer or semi-trailer
Designed for mid&short distance standard transportation on paved road at mid-low speed



Low Heat
Buildup



Self-
Cleaning



High
Load

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11.00R20	18	152/149	J	K	1078	282	15.0	3550	930	3250	930	8.0



A66/GK90 **A66+/A990**



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on mixed road at low speed



Anti-puncture

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
10.00R20	18	149/146	J	D	1068	278	24.5	3250	930	3000	930	7.5
11.00R20	18	152/149	J	D	1088	286	25.0	3550	930	3250	930	8.0
12.00R20	20	156/153	L	D	1130	310	24.0	4000	900	3650	900	8.5



A903



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on rough roads at mid low speed



Low Heat
Buildup



Anti-
puncture



Grip

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
295/80R22.5	20	154/150	L	D	1052	295	21.0	3750	850	3350	850	9.00
295/80R22.5	20	154/150	L	J	1052	295	21.0	3750	850	3350	850	9.00



A905



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on rough roads at mid low speed



Low Heat
Buildup



Anti-
puncture



Grip

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R20	20	156/153	L	D	1130	310	24.0	4000	900	3650	900	8.50



UE06/GK06 A906



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on rough roads at low speed



Wear-
Resistant



Low Heat
Buildup



Scratch
Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11.00R20	20	153/150	L	D	1102	282	24.0	3650	970	3350	970	8.0
12.00R20	20	156/153	L	D	1134	304	24.0	4000	900	3650	900	8.5
12R22.5	18	152/149	J	F	1102	290	24.0	3550	930	3250	930	9.00
13R22.5	22	158/156	M	D	1134	307	24.0	4250	900	4000	900	9.75



E610/E611 A669



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on rough roads at mid low speed



Low Heat
Buildup



Anti-
puncture



Grip

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11.00R20	18	152/149	J	D	1092	282	24.0	3550	930	3250	930	8.0
12.00R20	20	156/153	L	D	1130	306	25.0	4000	900	3650	900	8.50



A907/A915/GK07

UE07/UE15/GK15



Suitable for only trailer or semi-trailer
Designed for short distance overload transportation
on bad gravel roads at low speed



Scratch
Resistance



Long-
Lasting

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11.00R20	20	153/150	L	D	1102	280	28.0	3650	970	3350	970	8.0
12.00R20	20	156/153	L	D	1134	302	26.0	4000	900	3650	900	8.5



KS001



Suitable for only trailer or semi-trailer
Designed for short distance overload transportation
on bad gravel roads at low speed



Scratch
Resistance



Long-
Lasting

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R20	20	156/153	L	D	1134	302	26.0	4000	900	3650	900	8.5



UE08/GK08 A908



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation
on unpaved road



Low Heat
Buildup



Self-
Cleaning



High
Load

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11.00R20	20	153/150	L	D	1102	282	26.0	3650	970	3350	970	8.0
12.00R20	20	156/153	L	D	1136	302	24.8	4000	900	3650	900	8.5
12R22.5	18	152/149	J	F	1102	290	26.0	3550	930	3250	930	9.00



GK13/KS009 A913



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation on
mixed road at low speed



Long-
Lasting



Anti-
puncture



Uneven
Wear Resistance

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R20	20	156/153	L	B	1147	306	33.5	4000	900	3650	900	8.5



GK16/K5005 A916



Suitable for only trailer or semi-trailer
Designed for short distance heavy load transportation on rough roads at low speed



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R20	20	156/153	L	D	1134	306	23.7	4000	900	3650	900	8.5



UE28/GK28 **A928/D902**



Suitable for only trailer or semi-trailer
 Designed for mid-short distance standard transportation
 on mixed road at mid speed

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12.00R24	22	162/159	M	D	1240	308	25.0	4750	970	4375	970	8.5
12.00R24	22	162/159	M	F	1240	308	25.0	4750	970	4375	970	8.5
12R22.5	18	152/149	J	K	1096	293	24.0	3550	930	3250	930	9.00
295/80R22.5	20	154/150	L	J	1050	295	21.0	3750	850	3350	850	9.00
315/80R22.5	22	161/157	M	D	-	-	25.0	4625	900	4125	900	9.00



A501



Suitable for only trailer or semi-trailer
Designed for Urban and intercity short distance transport on paved road at mid speed



Wear-Resistant

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
		Single/Dual			Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	1092	305	21.5	3550	930	3250	930	9.00
11R22.5	16	148/145	H	J	1060	282	22.0	3150	850	2900	850	8.25
275/70R22.5	18	152/149	J	J	962	280	22.5	3550	900	3250	900	8.25



A503



Suitable for only trailer or semi-trailer
Designed for Urban and intercity short distance transport
on paved road at mid speed



Self-Cleaning



High Load



Anti-Skidding

**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index Single/Dual	Load Range	Speed	Designed		Tread Depth	Single		Dual		Standard Rim
					Outer Diameter	Section Width		(Kg)	(kpa)	(Kg)	(kpa)	
11R22.5	16	148/145	H	J	1060	282	22.0	3150	850	2900	850	8.25
275/70R22.5	18	150/145	J	J	962	280	22.0	3350	900	2900	900	8.25
295/80R22.5	18	152/149	J	K	1051	292	21.0	3550	900	3250	900	9.00



UE12/GK12 **A912**

Suitable for only trailer or semi-trailer



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Tread Depth	Single		Dual		Standard Rim
		Single/Dual				(Kg)	(kpa)	(Kg)	(kpa)	
12.00R20	20	156/153	L	D	20.8	4000	900	3650	900	8.50



A708/G208

Suitable for only trailer or semi-trailer



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Tread Depth	Single		Dual		Standard Rim
		Single/Dual				(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	20.5	3550	930	3250	930	9.00



A710 /G210

Suitable for only trailer or semi-trailer



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Tread Depth	Single		Dual		Standard Rim
		Single/Dual				(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	20.5	3550	930	3250	930	9.00



A617/G117

Suitable for only trailer or semi-trailer



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Tread Depth	Single		Dual		Standard Rim
		Single/Dual				(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	18.7	3550	930	3250	930	9.00



A517/G017

Suitable for only trailer or semi-trailer



**This product cannot be used for lorries truck and buses.*

Size	PR	Load Index	Load Range	Speed	Tread Depth	Single		Dual		Standard Rim
		Single/Dual				(Kg)	(kpa)	(Kg)	(kpa)	
12R22.5	18	152/149	J	L	19.8	3550	930	3250	930	9.00